

Hallmark Frost

Construction Specification

- Full overlay door with modified overlay on wall cabinets
- • Door / drawer stiles and rails are $\frac{3}{4}$ " thick and $2\frac{1}{4}$ " wide
- $\frac{1}{2}$ " thick MDF raised center panel
- 5-piece recessed panel drawer front matches door design
- Doors and Drawer Fronts: Doors and drawer fronts in the Value line are made of solid wood rails joined together with mortise and tenon joints with an MDF center panel to reduce the possibility of shrinkage and is the preferred material for painted finishes. Drawer fronts have solid wood rails with a recessed center panel.
- Hinges: Compact Blumotion soft-close mechanism integrated in concealed six-way adjustable hinges. Hinges open at 110° . Please note: Lazy Susan, Easy Reach and Pie Cut cabinets do not feature the soft-close mechanism.
- Drawers: The Value line includes a $\frac{5}{8}$ " thick solid wood dovetail drawer box with a $\frac{3}{8}$ " plywood bottom attached to Tandem plus Blumotion full extension soft-closing concealed drawer runners. Interior drawer height is $2\frac{1}{2}$ ".
- Shelving: 15mm ($\frac{5}{8}$ ") thick select veneered plywood with matching wood edge-banding is used on all wall, tall, and base cabinetry where applicable. The adjustable shelves are supported by plastic self-locking shelf clips. All standard depth base cabinetry includes an $11\frac{7}{8}$ " deep adjustable shelf, wall cabinetry $10\frac{5}{8}$ " deep adjustable shelves, and tall cabinetry 18" deep adjustable shelves.
- Backs, Tops and Bottoms: $\frac{1}{2}$ " thick veneered plywood with natural finished interiors grooved to face frame. The backs are stapled and screwed into place for additional support.
- Toe Kick: Base and tall cabinets are constructed with $\frac{3}{4}$ " x $4\frac{1}{2}$ " plywood toe kick. Additional 8-foot lengths of $\frac{1}{4}$ " toe kicks are available in matching colors to our cabinetry.
- Panel Beams: A $2\frac{1}{2}$ " x $\frac{1}{2}$ " plywood panel beam is fastened into a dovetail groove at the top of each base cabinet to ensure a straight fully integrated side, and for use of support and mounting of a countertop.
- Finished ends are applied with select Medium-density fibreboard panels